

STANDARD ROUTER:

MODEL	WORKING AREA (XYZ)	WORK SPEED	RAPID SPEED	MULTI HEADS
STANDARD 13*25	1300*2500*250 mm	14 m/min	15	UP TO 4
STANDARD 15*25	1500*2500*250 mm			
STANDARD 15*30	1500*3000*250 mm			
STANDARD 15*35	1500*3500*250 mm			
STANDARD 20*25	2000*2500*250 mm			UP TO 8
STANDARD 20*40	2000*4000*250 mm			
STANDARD 25*25	2500*2500*250 mm			
STANDARD 25*40	2500*4000*250 mm			

STANDARD CONFIGURATION				
DRIVE SYSTEM	High Power Stepper Motors		High functional Servo Motors	
INSTALLATION SURFACE	T-slot		Spoil Boards	
LINEAR RAILS	HIWIN		TBI	
CONTROLLER SYSTEM	Mach3	NC-Studio	DSP	linuxcnc Parallel
CONTROL PANEL	French Schneider Electronic Parts			
VOLTAGE	220V		380V	
OPTIONAL ITEMS				
SPINDLE MOTOR	HSD 4.5, 6 or 9 HP			
	HSD ATC 12 HP			
	Water Cooled 1:9 HP			
	Air Cooled 2:9 HP			
ADD-Ons				
HEAD	Dual Head			
	Pneumatic spindle			
	ATC			
	C-axis			
	B-axis			
ROTARY	125mm internal			
	250*2500mm External Router			
Cutter plotter				
2D Scanner				
Vacuum Cup				
Vacuum Table				
Roller Hold Down				